

U.S. Serial No. 10/571,044  
Reply to Office Action of May 21, 2008  
Amendment dated: August 15, 2008

RECEIVED  
CENTRAL FAX CENTER  
AUG 15 2008

**AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A backlight for a display device comprising:  
a light source for emitting light, and

a diffuser disposed between the light source and a liquid crystal display device, wherein the diffuser is comprised of a continuous body of a first resin material and diffusion elements, each of the diffusion elements being comprised of a body of a second resin material different from the first resin material, and the diffusion elements are located within the continuous body of the first resin material and are completely surrounded and encapsulated by portions of the first resin material such that each of the diffusion elements has a portion of the first resin material located at a light incident side and a portion of the first resin material at a light emission side.

2. (Previously Presented) The backlight as described in claim 1, characterized in that:

said diffuser further includes a light distribution layer having a prismatic surface facing toward the liquid crystal display device.

Claim 3. (Canceled)

4. (Previously Presented) The backlight as described in claim 1, characterized in that:

said first resin material and said second resin material are resin materials having refractive index ranging from 1.2 to 1.7.

Claim 5. (Canceled)

U.S. Serial No. 10/571,044  
Reply to Office Action of May 21, 2008  
Amendment dated: August 15, 2008

6. (Previously Presented) The backlight as described in claim 1, characterized in that:

said diffuser further comprises a light receiving portion for receiving the light emitted from the light source, formed integrally with the diffuser, and disposed more toward the light source than the diffuser.

7. (Previously Presented) The backlight as described in claim 6, characterized in that:

said light receiving portion has a prismatic shape on a surface thereof facing to said light source.

Claim 8. (Canceled)

9. (Previously Presented) The backlight as described in claim 6, characterized in that:

said light receiving portion is composed of said first resin.

Claims 10.-11. (Canceled)

12. (Withdrawn) A method for manufacturing a diffuser of a backlight provided for a liquid crystal display device for illuminating thereof, said method characterized by comprising:

a first charging step of charging a first resin into a first cylinder;

a second charging step of charging the first resin into which a second resin different from the first resin is mixed, into a second cylinder;

a first molding step of molding a two-layered sheet including the first resin and the first resin into which the second resin is mixed, by multi-layer extrusion molding, using the first cylinder into which the first resin is charged by the first charging step and the second cylinder into which the first resin into which the second resin is mixed is charged by the second charging step; and

U.S. Serial No. 10/571,044  
Reply to Office Action of May 21, 2008  
Amendment dated: August 15, 2008

a second molding step of molding a surface of the first resin of the sheet molded by the first molding step, into a prismatic shape by surface rolling.

13. (Withdrawn) A method for manufacturing a diffuser of a backlight provided for a liquid crystal display device for illuminating thereof, said method characterized by comprising:

- a first charging step of charging a first resin into a first cylinder;
- a second charging step of charging the first resin into which a second resin different from the first resin is mixed, into a second cylinder;
- a third charging step of charging the first resin into a third cylinder;
- a first molding step of molding a three-layered sheet by multi-layer extrusion molding, using the first cylinder into which the first resin is charged by the first charging step, the second cylinder into which the first resin into which the second resin is mixed is charged by the second charging step, and the third cylinder into which the first resin is charged by the third charging step, wherein the three-layered sheet is formed from the first resin, the first resin into which the second resin is mixed, and the first resin, with both exposed layers thereof being formed from the first resin;

- a second molding step of molding a surface of one of the first resin-formed layers of the sheet molded by the first molding step into a prismatic shape by surface rolling; and

- a third molding step of molding a surface of other one of the first resin-formed layers of the sheet molded by the first molding step into a prismatic shape by surface rolling.

14. (Withdrawn) A method for manufacturing a diffuser of a backlight provided for a liquid crystal display device for illuminating thereof, said method characterized by comprising:

- a mixing step of mixing a second resin into a first resin;
- a first molding step of molding the first resin into which the second resin is mixed by the mixing step, into a sheet; and

U.S. Serial No. 10/571,044  
Reply to Office Action of May 21, 2008  
Amendment dated: August 15, 2008

a second molding step of molding a prism-shaped first resin by using a 2P molding method in contact and integral with one of surfaces of the sheet molded by the first molding step.

15. (Withdrawn) The method for manufacturing a diffuser as described in claim 14, characterized by further comprising:

a third molding step of molding a prism-shaped first resin by using a 2P molding method in contact and integral with other one of surfaces of the sheet molded by the first molding step.

16. (Currently Amended) A liquid crystal display apparatus comprising:  
a liquid crystal portion; and

a backlight for illuminating the liquid crystal portion,

wherein said backlight includes a light source for emitting light, and a diffuser disposed between the light source and the liquid crystal portion,

wherein said diffuser is comprised of a continuous body of a first resin material and diffusion elements, each of the diffusion elements being comprised of a body of a second resin material different from the first resin material, and the diffusion elements are located within the continuous body of the first resin material and are completely surrounded and encapsulated by portions of the first resin material such that each of the diffusion elements has a portion of the first resin material located at a light incident side and a portion of the first resin material at a light emission side.

17. (Original) The liquid crystal display apparatus as described in claim 16, characterized in that:

said diffuser further comprises a light focusing layer for focusing the light emitted from the light source, formed integrally with the diffusion layer, and disposed more toward the light source than the diffusion layer.

U.S. Serial No. 10/571,044  
Reply to Office Action of May 21, 2008  
Amendment dated: August 15, 2008

18. (Withdrawn) A backlight provided for a liquid crystal display device for illuminating thereof, characterized by comprising:

a light source for emitting light; and

a diffuser disposed between the light source and the liquid crystal display device,

wherein said diffuser includes a light focusing layer for focusing the light emitted from the light source, and a light distribution layer integrally formed with the diffusion layer and disposed more toward the liquid crystal display device than the light focusing layer, for distributing the light focused by the light focusing layer toward the liquid crystal display device, and

wherein said focusing layer has a prismatic shape on a surface thereof facing to said light source, said prismatic shape being composed of a plurality of different shaped prism defined by the distance from said light source.

19. (Withdrawn) The backlight as described in claim 18, characterized in that:

said light distribution layer has a prismatic surface on a surface thereof facing toward the liquid crystal display device.

Claim 20. (Canceled)

21. (Withdrawn) A liquid crystal display apparatus characterized by comprising:

a liquid crystal display device; and

a backlight for illuminating the liquid crystal display device,

wherein said backlight includes a light source for emitting light, and a diffuser disposed between the light source and the liquid crystal display device,

wherein said diffuser includes a light focusing layer for focusing the light emitted from the light source, and a light distribution layer integrally formed with the light focusing layer and disposed more toward the liquid crystal

U.S. Serial No. 10/571,044  
Reply to Office Action of May 21, 2008  
Amendment dated: August 15, 2008

display device than the light focusing layer, for distributing the light focused by the light focusing layer toward the liquid crystal display device, and

wherein said focusing layer has a prismatic shape on a surface thereof facing to said light source, said prismatic shape being composed of a plurality of different shaped prism defined by the distance from said light source.

22. (Withdrawn) A light guide plate having a light incidence surface, for guiding light emitted from a plurality of light emitting devices arranged in a row at predetermined intervals in a longitudinal direction of the light incidence surface for surface emission, characterized in that:

a gate through which a molten material is charged to fill a cavity of an injection molding die during injection molding of the light guide plate is disposed at a position of the light incidence surface where none of the plurality of light emitting devices are arranged.

23. (Withdrawn) A light guide plate having a light incidence surface, for guiding light emitted from a plurality of light emitting devices arranged in a row at predetermined intervals in a longitudinal direction of the light incidence surface for surface emission, and being wedge-shaped with a thickness thereof gradually decreasing in a direction of guiding the guided light, characterized in that:

a gate through which a molten material is charged to fill a cavity of an injection molding die during injection molding of the light guide plate is arranged at a position of the light incidence surface where none of the plurality of light emitting devices are arranged.

24. (Withdrawn) The light guide plate as described in claim 23, characterized in that:

if a plurality of light emitting devices having an even number are arranged in a row at predetermined intervals in a longitudinal direction of the light incidence surface for surface emission, said gate is arranged at a position

U.S. Serial No. 10/571,044  
Reply to Office Action of May 21, 2008  
Amendment dated: August 15, 2008

between two of the light emitting devices located near the center of the longitudinal direction of the light incidence surface, where none of the plurality of light emitting devices are arranged.

25. (Withdrawn) The light guide plate as described in claim 23, characterized in that:

if a plurality of light emitting devices having an odd number are arranged in a row at predetermined intervals in a longitudinal direction of the light incidence surface for surface emission, said gate is arranged at a position between a light emitting device located at the center of the longitudinal direction of the light incidence surface, and one of light emitting devices adjacent to said light emitting device located at the center, where none of the plurality of light emitting devices are arranged.

26. (Withdrawn) The light guide plate as described in claim 23, characterized in that:

said plurality of light emitting devices are light emitting diodes (LEDs).

27. (Withdrawn) A backlight characterized by comprising:

a light guide plate for guiding light incident on a light incidence surface for surface emission from a light emergence surface;

a light source having a plurality of light emitting devices arranged in a row at predetermined intervals in a longitudinal direction of the light incidence surface of the light guide plate;

a reflection sheet disposed on a side of a light reflection surface of the light guide plate;

a sheet member formed from a diffusion sheet and a prism sheet disposed so as to be stacked on a side of the light emergence surface of the light guide plate; and

a frame for holding the light source, the reflection sheet, and the sheet member on the light guide plate,

U.S. Serial No. 10/571,044  
Reply to Office Action of May 21, 2008  
Amendment dated: August 15, 2008

wherein the light guide plate has a gate, through which a molten material is charged to fill a cavity of an injection molding die during injection molding of the light guide plate, disposed at a position of the light incidence surface where none of the plurality of light emitting devices are arranged.

28. (Withdrawn) A backlight characterized by comprising:

a light guide plate for guiding light incident on a light incidence surface for surface emission from a light emergence surface, and being wedge-shaped so that a thickness of the light guide plate gradually decreases in a direction of guiding the guided light;

a light source having a plurality of light emitting devices arranged in a row at predetermined intervals in a longitudinal direction of the light incidence surface of the light guide plate;

a reflection sheet disposed on a side of a light reflection surface of the light guide plate;

a sheet member formed from a diffusion sheet and a prism sheet disposed so as to be stacked on a side of the light emergence surface of the light guide plate; and

a frame for holding the light source, the reflection sheet, and the sheet member on the light guide plate,

wherein the light guide plate has a gate, through which a molten material is charged to fill a cavity of an injection molding die during injection molding of the light guide plate, disposed at a position of the light incidence surface where none of the plurality of light emitting devices are arranged.

29. (Withdrawn) The backlight as described in claim 28, characterized in that:

if the plurality of light emitting devices of the light source, having an even number are arranged in a row at predetermined intervals in a longitudinal direction of the light incidence surface for surface emission, the light guide plate has the gate arranged at a position between two of the light emitting devices



U.S. Serial No. 10/571,044  
Reply to Office Action of May 21, 2008  
Amendment dated: August 15, 2008

located near the center of the longitudinal direction of the light incidence surface, where none of the plurality of light emitting devices are arranged.

30. (Withdrawn) The backlight as described in claim 28, characterized in that:

if the plurality of light emitting devices of the light source, having an odd number are arranged in a row at predetermined intervals in a longitudinal direction of the light incidence surface for surface emission, the light guide plate has the gate arranged at a position between a light emitting device located at the center of the longitudinal direction of the light incidence surface, and one of light emitting devices adjacent to the light emitting device located at the center, where none of the plurality of light emitting devices are arranged.

31. (Withdrawn) The backlight as described in claim 28, characterized in that:

said plurality of light emitting devices of the light source are light emitting diodes (LEDs).

32. (Withdrawn) A method for manufacturing a light guide plate having a light incidence surface, for guiding light emitted from a plurality of light emitting devices arranged in a row at predetermined intervals in a longitudinal direction of the light incidence surface for surface emission, characterized in that:

the light guide plate is injection-molded by charging a molten material for filling a cavity of an injection molding die through a gate disposed at a position of the light incidence surface where none of the plurality of light emitting devices are arranged.

33. (Withdrawn) A method for manufacturing a light guide plate having a light incidence surface, for guiding light emitted from a plurality of light emitting devices arranged in a row at predetermined intervals in a longitudinal

U.S. Serial No. 10/571,044  
Reply to Office Action of May 21, 2008  
Amendment dated: August 15, 2008

direction of the light incidence surface for surface emission, and being wedge-shaped with a thickness thereof gradually decreasing in a direction of guiding the guided light, characterized in that:

the light guide plate is injection-molded by charging a molten material for filling a cavity of an injection molding die through a gate disposed at a position of the light incidence surface where none of the plurality of light emitting devices are arranged.

34. (Withdrawn) The method for manufacturing a light guide plate as described in claim 33, characterized in that:

if a plurality of light emitting devices having an even number are arranged in a row at predetermined intervals in a longitudinal direction of the light incidence surface for surface emission,

the light guide plate is injection-molded by charging a molten material for filling a cavity of an injection molding die through the gate arranged at a position between two of the light emitting devices located near the center of the longitudinal direction of the light incidence surface, where none of the plurality of light emitting devices are arranged.

35. (Withdrawn) The method for manufacturing a light guide plate as described in claim 33, characterized in that:

if a plurality of light emitting devices having an odd number are arranged in a row at predetermined intervals in a longitudinal direction of the light incidence surface for surface emission,

the light guide plate is injection-molded by charging a molten material for filling a cavity of an injection molding die through the gate arranged at a position between a light emitting device located at the center of the longitudinal direction of the light incidence surface, and one of light emitting devices adjacent to said light emitting device located at the center, where none of the plurality of light emitting devices are arranged.